

Features

- Super Smooth
- Prevents light transparency and shadowing
- Matte surface available / **Double Sides Printable**
- Best suited for pop-up, roll-up, x-displays, and an array of close viewing indoor applications

Applications



Technical Data Sheet

Item Code		FBDBGL530DS	Test Method
Total Weight (GSM)		530	DIN53352 BS342
PET Weight (GSM)		130	DIN EN ISO2286-2
PVC Weight (GSM)		400	DIN EN ISO2286-2
Thickness (MM)		0.35	---
Tensile Strength	Warp (N/5cm)	1280	ISO527/3:1995
	Weft (N/5cm)	1130	ISO527/3:1995
Tear Strength	Warp (N)	200	ISO4674/1:2003
	Weft (N)	190	ISO4674/1:2003
Adhesion Strength (N/5cm)		60	DIN53357 BS3425
Temperature		-30°C/+70°C	ISO13934-1:1999

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility with respect to factors that are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■

	Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District, Haining, Zhejiang, China Tel: +86-573-80776996 Fax: +86-573-80776998 Mob/Skype/Wechat: +86-15858322153 mailto:contact@hncomax.com https://www.hncomax.com	
---	---	---